

Universe	Sport
Type	Verticality
Category	Carabiners and quickdraws
Subcategory	Locking carabiners



Sm'D

Sm'D is a D-shaped locking carabiner that is lightweight, and compact, and can be used in numerous situations; it is easy to manipulate, even when wearing gloves, and is available in two locking system versions.



TWIST-LOCK locking system: specific use when quick opening is key (e.g. at the end of a lanyard) and when connecting a GRIGRI to the harness.



Hole allows a TIBLOC to be connected to the carabiner with a cord, making the device loss-proof.



Hole allows a MICRO TRAXION to be connected to the carabiner with a cord, making the device loss-proof.

Short Description Very versatile, lightweight, compact, D-shaped locking carabiner



Selling Points

- Great versatility:
 - D shape guarantees efficiency in any situation, thus responding to multiple uses: connection to a belay system to a pulley, or to the end of a lanyard...
 - compact and very lightweight
- Good handling and ergonomics:
 - D shape for good handling
 - H profile contributes to better grip when wearing gloves
 - Keylock system to avoid any involuntary snagging of the carabiner
 - hole allows a TIBLOC or a MICRO TRAXION to be connected to the carabiner with a cord, making these devices loss-proof
- Available in two locking systems, each for different situations:
 - SCREW-LOCK: easy-to-open system, locking or not, according to the need of the user. The red band provides a visual warning when the carabiner is unlocked. This system is suitable for difficult environments where contaminants (mud, ice) could cause an automatic locking system to jam.
 - TWIST-LOCK: specific use when quick opening is key (e.g. at the end of a lanyard) and when connecting a GRIGRI to the harness

Specification

- Material(s): aluminum
 - Certification(s): CE EN 12275, UIAA
-

Specifications by reference

Reference(s)	M39A SL	M39A RL
		
Weight	46 g	51 g
Locking system	SCREW-LOCK	TWIST-LOCK
Type	B	B
Color(s)	yellow	yellow
Major axis strength	23 kN	23 kN
Minor axis strength	8 kN	8 kN
Open gate strength	7 kN	7 kN
Gate opening	20 mm	20 mm
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	20	20
EAN	3342540817524	3342540817548

Related product(s) DUAL CONNECT ADJUST
REVERSO® 4
GRIGRI® +
TIBLOC
MICRO TRAXION