SRE 9046 TC

Paraffin laser heater



Product data sheet

Product category	Paraffin laser heaters
Brand	Qlima
Model	SRE 9046 TC
Colour	White
EAN code	8713508790787

Technical specifications

• • • • • • • • • • • • • • • • • • •			
Burner type		Electronic Injection Burner System (BI)	
Capacity (min./max.)	kW	1,28 / 4,65	
For rooms up to	m²	30 - 76	
	m³	75 - 190	
Consumption (max.)	l/h	0,485	
	g/h	388	
Capacity tank	I	9	
Autonomy (min./max.)	h	18 - 67	
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1	
Power consumption at start	W	428	
Power consumption	W	88 - 175	
Sound pressure level	dB(A)	25 - 39	
Dimensions (w x d x h) ¹	mm	466 x 349 x 445	
Net. weight	kg	13	
Warranty ²	years	4	
Safety features		Tip-over switch - Safety stop - Overheat protection - Safe top - Child lock	


Package content

Paraffin laser heater, Syphon pump, Transport cap, User manual

Accessories (not included)

Description	•	,	EAN code







WxDxH= 52 x 41 x 52 cm



Gross weight 15 kg



protection - Safe top - Child lock

¹ including base plate

² except manual fuel pump

SRE 9046 TC

Paraffin laser heater



Tip-over safety switch



Daytimer



Energy saving mode



Advanced control system



Frost protection



Child lock



Adjustable thermostat



Safety stop



Made in Japan

Smart Save mode: The 'SAVE' function allows you to keep the set temperature in the room. This saves on the energy consumption.

Anti-freeze function : Install the save mode at the lowest temperature setting (5°C) to activate the freezing prevention function.

Fuzzy logic: This heater is equipped with a self-regulating temperature control system. The heating mode can be set according to the requirements.

High-tech burner: This heater is equipped with a burner system that heats up extremely quick and very gradual. This gives a more comfortable heating sensation.

Semi-automatic operation: This heater is equipped with a 24-hour programmable timer and integrated thermostatic control to maintain the desired room temperature.

Safety system: This heater is fitted with a safety system that automatically switches off the heater after approximately 56 hours of continuous operation. Use the safety stop to switch off the heater inmediately.

3 hour timer: The device will automatically turn off after 3 hours of usage.

Automatic airflow control: The speed of the built-in fan is self-regulatory, depending on the burning mode of the heater.

Wickless design: Provides clean and economical heating without wick maintenance or replacement.

Information display: The digital displays helps to keep track of all the important heater functions.

Safe top: The temperature of the top plate is kept relatively low for improved safety.

Childproof lock: When this button is pressed, the operation of buttons will be blocked, except the on/off button.

Manual fuel syphon pump: This heater is delivered with a convenient pump to fill the fuel tank.

Automatic extension operation mode: When the fuel tank is almost empty, the display will show that the tank has to be refilled. The extension operation mode is activated and the heater switches to the lowest burning mode for more than one hour.

Large autonomy: The large 9 I fuel tank is good for up to ||MaxAutonomy|| hours of pleasant heat.

Additional heat output: All consumed electric energy is emitted in the room to be heated.

Anti-odour system: The perfectly balanced heating system burns almost 100% of all fumes and gasses throughout the complete combustion process (start up - heating - cooling down). The result is a comfortable heating experience without unpleasant odours.

Easy touch cap: A new way to easily mount the removable fuel tank cap without touching the tank directly.

Quiet operation: When heating the room, the device produces only a limited amount of sound. Also in the start up phase, the heater produces very little sound.

Transport cap: Essential for the transport of your device, it is included in the box.

Recyclability: Over 90% of the heater can be recycled.

Warranty: 4 year warranty, excluding the pump

Made in Japan: This heater has been produced according to the ISO 9000:2015 Quality Control Standard.